

Manomètre sec boîtier acier



FIG 1112V = Raccord vertical
FIG 1112A = Raccord axial

- Classe 2,5
- IP 43
- Boîtier en acier
- Tube bourdon
- Raccord en laiton
- Verre acrylique incassable
- Température de service : -20°C à +60°C
- Conforme à la Norme EN 837-1

Dimensions

Ø Boîtier Ø Raccord	63 1/4"	80 1/2"	100 1/2"	160 1/2"
	-1/0 b	-1/0 b	-1/0 b	-1/0 b
	-1/0.6 b	-1/0.6 b	-1/0.6 b	-1/15 b
	-1/1.5 b	-1/1.5 b	-1/1.5 b	0/1 b
	-1/3 b	-1/3 b	-1/3 b	0/1.6 b
	-1/5 b	-1/5 b	-1/5 b	0/2.5 b
	-1/9 b	-1/9 b	-1/9 b	0/4 b
	0/1 b	0/1 b	-1/15 b	0/6 b
	0/1.6 b	0/1.6 b	0/1 b	0/10 b
	0/2.5 b	0/2.5 b	0/1.6 b	0/16 b
	0/4 b	0/4 b	0/2.5 b	0/25 b
	0/6 b	0/6 b	0/4 b	0/40 b
	0/10 b	0/10 b	0/6 b	
	0/16 b	0/16 b	0/10 b	
	0/25 b	0/25 b	0/16 b	
	0/40 b	0/40 b	0/25 b	